



## SPECIFICATON

Voltage:110V/220V

Frequency:50-60HZ

Power consumption:30W

lamp:led

Motor:12V26rmp

Color:4main color(R.G.B.W)

Size:500\*220\*320mm

weight:5KG

Features:pan/tit can rotate unlimitedly. This mode has the advantages of low power consumption and very safty for operation.it is quite suitable for using at middle or small size KTV room restaurant, and bars besides, It can keeping on working all night without pause that make it an ideal choice for stage using in the 21th century.



Working voltage:24V/110-220V

LED color: red yellow blue green white

Lamp power: 12W

Protective level: IP65

Materials: stainless steel



12-channel DMX-512 Led moving yoke

pan 540 tilt 270

LEDSource:1W\*18pcs RGB color mixing

variable electronic dimmer(0-100%)

vector-in movement macros via master/slave or DMX controller

user-selectable basic or advanced operating modes

user-selectable pan/tilt ranges

pan:540,360,180

Tilt:270,180,90

compact and lightweight LED display menu with invert

reset to factory settings option

display auto on/off

pan/tilt invert option

Fan cooled

Easy controller



Accept DMX512 signal, can run automatically by itself or connect with other light, adopt photo electricity reposition system.

Power supply: AC220V50HZ

Power:50w

Lamp: 86\*1WLED

Strobe:1-20times/second

Color:RGB nonpolar color-mixed system.

level scanning :540°+tiny adjust

perpendicular : 300°+ tiny adjust

size: 260×210×270mm

weight: 9. 8KG



## 250W MOVING SPOT

### SKILL SPECIFICATIONS

Power: 220V/50Hz(standard)

(The other power can order)

Lamp: NSD 250W

Power Consumption: 400W

Control Signal: DMX 512

Control Channels: 8CH

(The other channel can order)

Motors: 9

Carton Size: L435\*W415\*H575(mm)

N.W: 23.5 KG

G.W: 27 KG

#### PERFORMANCETRAIT

8 colors, achieving high speed double way rainbow and scrolling effect

8 changeable patterns(including 2 glass pattern),achieving freely adjusting fast and low speed flowing water scrolling effect, smooth scanning action and quiver at no time

Pattern internal rotting function, freely adjusting fast, low speed, clockwise and anticlockwise

Mechanical linear DIMMER and 1-7 times/s STROBE effect

Horizontal 450° and vertical 252° scanning range, smooth scanning action and accurate orientation

Precise adjustment on horizontal and vertical position

Music startup and self group online runs according to the building program , no need of external controller

2 convection cooling-fan, optimize internal air duct way, heat elimination rapidly

According to various kinds of safety standards,IP20 protect grades, The cable accords to the CE20/22 standard



Voltage:AC110-240V/50-60Hz

Power consumption:60W

Light source:54/108pcs high brightness LED

Packing size:510X380X380mm

Net weight:12kg

Gross Weight:13kg



Voltage: 110-220V/50-60HZ

Power: 60W

Color: 6

Size: 260×210×160mm

Weight: 2.3kg



4000B/5000B MOVING HEAD TO CHANGE THE COLOR SEARCH LIGHT

SKILL SPECIFICATIONS

Power supply:AC220V/280V 50-60Hz

Power consumption:4KW-5KW

Input voltage:AC220V/50Hz

Input current:56A-72A

Water proof grade:IP55

Lamp spec:Xenon lamp 1KW-5KW

Lamp life expectancy:600 hours

(light declines after 500 hours)

Intensity of electricity resistance:1.5KV

Insulation resistance:>2MΩ

Control mode:Stand-alone mode

Colour effect:CMY color mix system

Adjustment angle:Auto adjust

Light beam angle:0.6°-0.8°

Range:3-8km

Measurement:680x790x1430mm

Flight Case:770mmx860x1490mm

Net Weight:105kg

Gross Weight:175kg

Suitable place

It is widely used in TV Station,Outdoor performance,High Buildings,Gymnasium,Big Hotel,Park Greenbelt,Amusement Park,Travel industry sites



LED light source:252high-brightness  $\Phi$  5  
LED,red.Green.Blue.Four color tran  
sformationMaster-slave mode .Automatic  
mode Voice-activated mode(voice  
adjustable sensitivity)DMX512standard  
controlsignals,3DMX channels.There are  
rotating lights and chase results  
Power supply:AC100V/120V-220V/240V  
50/60HZ  
The total power:35W



Working voltage:24V/110-220V

LED color: red yellow blue green white

Lamp power: 54W

Protective level: IP65



Working voltage: 24V/110-220V

LED color: red yellow blue green white

Lamp power: 6W 12W

Protective level: IP65



Working voltage:24V/110-220V

LED color: red yellow blue green white

Lamp power: 24W

Protective level: IP65