



Product Description

KEY FEATURES:

1. Karaoke system, karaoke power amplifier, digital power amplifier, KTV system, pro audio
2. Digital Echo Karaoke Power Amplifier.(350W+350W)
3. Built-in Automatic Mute Circuit
4. Built-in Digital Echo Control Circuit
5. Group Inputs
6. Video synchronous switchover controller.
7. Built-in switching power supply& digital amplification module
8. Over electrical current & voltage protection

SPECIFICATION

Model	GX-350
Type	Karaoke Power Amplifier(2U)
Voltage	AC220V/50-60Hz
Related Power	350W+350W/8ohms 500W+500W/4ohms
Frequency Response	20Hz-20KHz
Distortion	≤0.05%
Tone control of treble and bass	BASS: ±8dB TREBLE: ±8dB
Input Sensitivity	>250mv
Max. Electricity Consumption	1000W
Dimension(HWD)	480×460×88mm
Packing Dimension(HWD)	540×530×190mm
Net Weight	10.5kg

DSP-8398/DSP-8398 DSP Karaoke processor



Product Description

24 bit digital key modulation and AD/DA converters

- ◆ Built-in 2 DSP music effects and 4 singing effects
- ◆ Digital tone control
- ◆ Reset function, return to the original singing automatically after finish each one song
- ◆ Can setup the volume of music and microphone when every time switch on by user's own motion
- ◆ Have locked function for max. output of music, microphone and sub-bass
- ◆ Intelligent sub-bass signal control (suitable for big and small size Karaoke room without management)
- ◆ a. Karaoke function: When switch on microphone, active bass and postposition output signal be attenuated automatically, attenuation volume can be setup
- ◆ b. Disco function: When switch off microphone, active bass and postposition output signal be reverted to output initialization in 3-5 seconds
- ◆ c. Locked function for active bass and postposition max. output volume
- ◆ Multiple input connectors, the first group is the default of the precedence for the KOD/VOD systems.
- ◆ Infrared remote control
- ◆ Input of multifunctional KTV controller, wired control connector for S terminal
- ◆ Automatic synchronization of video and audio switching
- ◆ 4 channels microphone input, 1 channel sub-bass output, 1 channel postposition output, 2 mixed main channel output
- ◆ Score output connector for mark the points on the screen
- ◆ Karaoke actuating effects selecting function (DSP-8398 have this function)
- ◆ Electron crossover function (DSP-8398 have this function) 5 channels output individually, the 2 postposition channels with the delay function (DSP-8389 have this function).

SPECIFICATIONS

Model	DSP_9398
Music Section	
Frequency Response	
S/N Ratio	>90dB
T.H.D	<0.01%
Input Sensitivity/Impedance	0.707V/47k Ohm
Max.Output	>85dB
High/Low (Increase/Attenuation)	±10dB
Key Modulation	Level ±4
Subwoofer Section	
Frequency Response	20Hz-15KHz (±2dB)
T.H.D	<0.07%
Microphone Section	
Frequency Response	50Hz-20kHz(±3dB)
S/N Ration	>80dB
T.H.D	<0.04%
Input Sensitivity/Impedance	100mv-500mv/4.7k Ohm
Dimension(HWD)	484×280×66 (mm)
Packing Dimension	535×390×125 (mm)
Net Weight	6.4kg

RV SERIES



Product Description

- ◆ User can setup the music volume, mic volume, echo depth and mic main volume to be auto lockup state. (RV-150C/200C/350C have this function)
- ◆ Have the function of control microphone whistle.
- ◆ Built-in automatic Karaoke noise proof circuitry.
- ◆ Built-in 16 bit digital tone adjusting controller. (RV-150C/200C/350C have this function) Microphone reverberation High and Low tone.
- ◆ Professional 20 bit digital echo circuitry to make the singing more richness and nature.
- ◆ Hidden knobs for adjusting the volume, tone and effect, well designed for Karaoke

room.

- ◆ The fan reinforce to disperse the heat for continuous working.
- ◆ Professional multi-mode digital reverberation, accurateness and trustiness by single-chip control.
- ◆ Multi- input connectors for different audio input.
- ◆ Safeguards against short-circuits, overload and the thermal runaway.
- ◆ Multiple input connectors, the first group is the default of the precedence for the KOD/VOD systems.
- ◆ Optional wired controller, more convenient for using.
- ◆ The input microphone jacks on front and rear panel.

Specifications:

Model	RV-350C	RV-200C	RV-150C	RV-200	RV-150	RV-100
Frequency Response	20Hz-20KHz±3dB	20Hz-20KHz±3dB	20Hz-20KHz±3dB	20Hz-20KHz±3dB	20Hz-20KHz±3dB	20Hz-20KHz±3dB
8 ohm stereo	2X350W	2X200W	2X150W	2X200W	2X150W	2X100W
4 ohm stereo	2X650W	2X350W	2X250W	2X350W	2X250W	2X150W
Power Consumption	1400W	800W	600W	800W	600W	400W
THD	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%
S/N Ratio	>85dB	>85dB	>85dB	>85dB	>85dB	>85dB
Power Supply	AC220V 50-60Hz	AC220V 50-60Hz	AC220V 50-60Hz	AC220V 50-60Hz	AC220V 50-60Hz	AC220V 50-60Hz
Dimensions	430X440X145 mm	430X360X145 mm	430X360X145 mm	430X360X145 mm	430X360X145 mm	430X360X145 mm
Packing Dimensions	485x475x200 mm	485x425x200 mm	485x425x200 mm	485x425x200 mm	485x425x200 mm	485x425x200 mm
Weight	18kg	14kg	13.5kg			

G SERIES



Product Description

SPECIFICATION:

Model	G-350C	G-200C	G-150C	G-200	G-150	G-100
Type	Karaoke Power Amplifier					
Power Output	2x350W 8 ohms 2x650W 4 ohms	2x200W 8 ohms 2x350W 4 ohms	2x150W 8 ohms 2x250W 4 ohms	2x200W8ohms 2x350W4ohms	2x150W8ohms 2x250W4ohms	2x100W8ohms 2x150W4ohms
T.H.D	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%
Frequency Response	20Hz-20KHz (±3dB)					
S/N Ratio	>85dB	>85dB	>85dB	>85dB	>85dB	>85dB
Music adjust	Bass 100 Hz ±8dB Treble 10KHz ±8dB					
Power Supply	AC220V 50-60Hz					

Power Consumption	800W	500W	400W	500W	400W	300W
Dimension(HWD)	145×440×430mm	145×440×430mm	145×440×430mm	145×440×430mm	145×440×430mm	145×440×430mm
Packing Dimension	210×490×490mm(0.05CBM)	210×490×430mm(0.044)	210×490×430mm(0.044)	210×490×430mm(0.044)	210×490×430mm(0.044)	210×490×430mm(0.044)
Gross Weight	17.2kg	12.6kg	11.8kg	12.4kg	11.2kg	10.2kg

MT SERIES



Product Description

◆ Shuttle electrograph separately control the mic , music volume and reverberation depth , with the project setting flexibly suitable for the project using.(MT-350C/MT-200C have this functions) .

◆ Have the function of restrain mic howling .

- ◆ Especially have the karaoke grading system easy for marking on screen .
- ◆ Built-in 16 bit digital tone modification adjusting control .
- ◆ Professional digital echo circuit ,make the human voice more natural and clear .
- ◆ Have the function of restrain microphone howling .Built -in 16 bit digital tone adjusting controller (MT-350C/MT-200C have this functions).Hidden knobs for adjusting the volume ,tone and effect ,well designed for karaoke room .
- ◆ Intelligent cooling system , changing the fan speed by temperature and reinforce to disperse the heat for continuous working .
- ◆ Multiple input connectors.
- ◆ The first group is the default of the precedence for the KOD/VOD systems.
- ◆ LCD screen with back light .
- ◆ Safeguard against short circuit and overloading.
- ◆ With the project setting flexibly suitable for the project using.
- ◆ Both rear and front panel have mic output socket ,easy for projecting fix-up and also with perfect appearance.

SPECIFICATION

Model	MT-350C	MT-200C	MT-150
Type	Karaoke Power Amplifier		
Power Output	2x350W 8 ohms 2x650W 4 ohms	2x200W 8 ohms 2x350W 4 ohms	2x150W 8 ohms 2x250W 4 ohms
T.H.D	≤0.1%	≤0.1%	≤0.1%
Frequency Response	20Hz~20KHz ±3dB	20Hz~20KHz ±3dB	20Hz~20KHz ±3dB
S/N Ratio	>85dB	>85dB	>85dB
Power Supply	AC220V 50~60Hz	AC220V 50~60Hz	AC220V 50~60Hz
Dimension(HWD)	145x440x430mm	145x430x360mm	145x430x360mm
Packing Dimension)	210x490x490mm(0.05CBM)	210x490x430mm(0.044CBM)	210x490x430mm(0.044CBM)
Gross Weight	17kg	12.6kg	

KTV SERIES



Product Description

- ◆ Professional setup functions can be adapt for any engineering projects. (Users could set up the music volume, mic volume, reverberation depth and Mic main volume, it will be started with the same setting when every time turn on the unit.
- ◆ Have the function of controlling microphone howling noise.
- ◆ Built-in 16-bit digital tone exchange adjusting controller(16 levels, each has 2.5 musical scales difference).
- ◆ Microphone reverberation with High and Low tone adjustment.
- ◆ Professional 20-bit digital echo circuitry to make the singing more rich and natural.

◆Hidden knobs for adjusting the volume, tone and effects, the completed well designed for Karaoke rooms.

◆The fan designed to change the rotary speed by temperature changing, it reinforce to disperse the heat for continuous working.

◆Full newly professional multi-mode digital reverberation, safety single-chip control.

◆Multiple input connectors for connecting different audio equipment.

◆Several music input groups special designed for Karaoke, the first group is the default one to match with the KOD/VOD computer systems. Safeguards against short-circuits and overload function.

◆Optional wired controller, more convenient for using.

◆The input microphone jacks have been designed on both front and rear panels.

Model	KTV-2350C	KTV-2200C	KTV-2150C
Type	Karaoke Power Amplifier	Karaoke Power Amplifier	Karaoke Power Amplifier
Power Output	2x350W 8 ohms 2x650W 4 ohms	2x200W 8 ohms 2x350W 4 ohms	2x150W 8 ohms 2x250W 4 ohms
T.H.D	≤0.1%	≤0.1%	≤0.1%
Music Adjust	Bass 100Hz ±8dB Treble 10KHz ±8dB	Bass 100Hz ±8dB Treble 10KHz ±8dB	Bass 100Hz ±8dB Treble 10KHz ±8dB
Frequency Response	20Hz-20KHz (±3dB)	20Hz-20KHz (±3dB)	20Hz-20KHz (±3dB)
S/N Ratio	>85dB	>85dB	>85dB
Power Supply	AC220V 50-60Hz	AC220V 50-60Hz	AC220V 50-60Hz
Power Consumption	800W	500W	400W
Dimension(HWD)	145x440x430mm	145x360x430mm	145x360x430mm

Packing Dimension	210×490×490mm(0.05CBM)	210×490×430mm(0.044CBM)	210×490×430mm(0.044CBM)
Net Weight	17.6kg	13kg	12kg

MKV SERIES



Product Description

Key Features:

- *Professional stereo digital tone modification makes the sound more natural.
- *Digital Feedback controller.
- *16bit digital tone controller .
- *Hidden knob design suitable for the karaoke Bar applications.
- *Intelligent cooling fan.
- *Multi-music inputs.
- *Priority inputs and compatible with KOD.
- *LCD displayer

- *Automatic volume and Mic settings Storage .
- *Overheat, short circuit and Dc fault protection .
- *Mic Outputs(front and rear).

SPECIFICATION

Model	MKV-350A	MKV-200A	MKV-150A
Type	Karaoke Power Amplifier	Karaoke Power Amplifier	Karaoke Power Amplifier
Power Output	2x350W 8 ohms 2x650W 4 ohms	2x200W 8 ohms 2x350W 4 ohms	2x150W 8 ohms 2x250W 4 ohms
T.H.D	≤0.1%	≤0.1%	≤0.1%
Frequency Response	20Hz-20KHz (±3dB)	20Hz-20KHz (±3dB)	20Hz-20KHz (±3dB)
S/N Ratio	>85dB	>85dB	>85dB
Power Supply	AC220V 50-60Hz	AC220V 50-60Hz	AC220V 50-60Hz
Dimension(HWD)	145x440x430mm	145x440x430mm	145x440x430mm
Packing Dimension)	210x490x490mm(0.05CBM)	210x490x430mm(0.044CBM)	210x490x430mm(0.044CBM)
Net Weight	15.8kg	12.6kg	

MOK SERIES



Product Description SPECIFICATION

Model	MOK-3.5W-3	MOK-3.5W-5	MOK-3.5W	MOK-2.0W	MOK-1.5W
Type	Karaoke Power Amplifier				
Power Output	2x350W+80W 8 ohms 2x650W+120W 4 ohms	2x350W+3x80W 8ohms 2x650W+3x120W 4ohms	2x350W 8 ohms 2x650W 4 ohms	2x200W 8 ohms 2x350W 4 ohms	2x150W 8 ohms 2x250W 4 ohms
T.H.D	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%
Frequency Response	20Hz-20KHz (±3dB)	20Hz-20KHz (±3dB)	20Hz-20KHz (±3dB)	20Hz-20KHz (±3dB)	20Hz-20KHz (±3dB)
S/N Ratio	>85dB	>85dB	>85dB	>85dB	>85dB
Power Supply	AC220V 50-60Hz				
Dimensions	150x460x430mm	150x460x430mm	150x460x430mm	150x430x410mm	140x430x410mm
Packing Dimensions	210x480x490mm(0.049CBM)	210x490x490mm(0.05CBM)	210x490x490mm(0.05CBM)	210x490x430mm(0.044CBM)	210x490x430mm(0.044CBM)
Gross Weight	19.2kg	19.4kg	17.8kg	14.6kg	13.2kg



The touch monitors allow you to freely maneuver between your favorite selections, select by Language, singers, male, female, group, generic, MV, sound effects...etc. Easy and fun for all ages. For commercial users, Accounting, Billing, food and beverage can also be built into the system.

點歌系統 (家庭版/單機版)

- 1、HITBOX 版本，增加了手寫功能，可以用鼠標，觸控屏等直接在顯示器上寫字點歌和歌星，方便快捷，只要你會寫字，就可以快速完成點歌操作；
- 2、完善了幻影功能，可以用純軟件實現電視機和顯視器同步播放唱歌畫面的功能，完善了加歌維護工具，可以直接在電腦上加歌，預播放，不需要接電視加歌；
- 3、免人值守，全自動，即點即播，無需等待；全自動的後台控制系統，免維護的後台控制系統，節省開支、避免人為錯誤。
- 4、自帶歌庫後台管理工具，日常維護和加歌、刪歌等更為簡單方便(用戶自己加或刪歌簡單快捷)；
- 5、增強了電視字幕 OSD 功能，支持在電視上廣播、預播放，操作提示、編號點歌等功能。
- 6、支持自定義界面，提供方便的工具，可以直接修改界面圖片和程序界面，拖拖拉拉，就是一套全新的界面出來，連風格都可以自由改變！，用戶可隨意打造(OEM)自己的點歌系統品牌；
- 7、包房電腦非法重啟後點歌系統自動恢復客人已點歌曲；
- 8、為使軟件適應更多不同的遙控器，提供用戶可以自由修改的遙控鍵碼設置功能，用戶無需要為購買何種遙控器而煩惱；
- 9、後台功能強大，操作簡便。
- 10、操作方便，支持點歌面板、遙控器、鼠標、觸摸屏以及手寫板等設備點歌。

2011Vod



This hi-tech console allows you to deliver up to 23,000 songs on demand. Full audio able to support Digital sound and high-definition video. Fully HD compatible

K-2010 karaoke box

HitBox K2 VISION-3.0 BY K-HOUSE HTPC & Karaoke System



最新遙控器

全新遙控器，高靈敏度接收器，獨特外型設計，
集合多功能於一身，專為 K-House System
(卡屋系列)而設。

快捷鍵：歌星、拼音、筆劃、粵曲、DVD、酒水等。
學習鍵：高低降、咪聲、音量...


HitBox Karaoke System:

本軟件是目前最流行的 VOD(視頻)點歌系統，功能強大，支持 VCD、DVD、MPG、DAT、MPEG 等音視頻格式播放(含電影、電視劇)。強大的查找(支持模糊查找及手寫歌名查找)功能，歌星、歌星等可任意添加、刪除，系統會自動識別；歌星查找(姓名、相片)支持姓名拼音識別漢字(帶聲調)；支持點歌自動排行；選歌、已點歌界面採用列表方式，可自由設置一屏列表歌曲數；可優先播放已選歌曲列表中的任意一首；提供現在時間、已點歌用時及播放進度顯示，管理員可無需登記開始點歌時間。系統管理支持更換任意點歌系統界面背景圖片、文字顏色、是否啟動操作系統后自動運行、右側滾動文字設置、管理密碼等。

后臺管理：歌庫添加支持多源文件，支持雙歌星加入，自動提取歌星姓名及性別并添加拼音、字數、歌名首字筆劃、類別等；支持刪除某歌、強大的備份、恢復功能，使你無后顧之憂；分類查找功能可根據條件詳細查找。
(本軟件適用於專業歌廳、酒店、卡拉OK廳、KTV、茶樓、酒吧、家庭等....)。

HitBox HTPC System:

全面提供全速率 藍光 音視頻支持 1080P 全高清、HDMI 次世代音頻 DRA/Dolby/DTS 環繞聲，一切 盡在其中。



KARAOKE4U

SUPPLIES OF ALL YOURS' KARAOKE NEEDS



Hard Drive Karaoke unit (Above),
either match with 17" / 19"
Touchscreen monitor (right) or
normal 19" TFT LCD monitor
(below) with remote



© 2003 CNET Networks, Inc.

